



mc 0,375
ft³ 13.2



kg 5,1
lb 11.2

Folk chair in ash-wood with a die-cast aluminium seat support, upholstered seat

Sedia Folk in frassino con supporto in pressofusione di alluminio e sedile imbottito / Stuhl FOLK aus Eschenholz mit Sitzschalen-Ring aus druckgußgegossenem Aluminium und gepolstertem Sitz / Chaise folk en frêne avec support en aluminium moule et assise revetue / Silla Folk en fresno con soporte de aluminio fundido a presión y asiento tapizado

MATERIALS

Materiali
Materialien
Matériaux
Materiales

• FRAME - TELAIO - STRUKTUR - STRUCTURE - ARMAZÓN

Ash-wood legs and ash plywood backrest

Gambe in frassino e schienale in multistrato di frassino / Beine aus Eschenholz und Rückenlehne aus Eschen-Multiplex / Pieds en frêne et arrière en multiplis de frêne / Patas de fresno y respaldo en contrachapada de fresno

WOOD FINISH - FINITURA LEGNO - HOLZ AUSFÜHRUNG - FINITION BOIS - ACABADO MADERA


Water-based paint, matt finish (5 gloss), anti-scratch

Verniciatura a base acqua, finitura opaca (5gloss), antigraffio / Lack auf Wasserbasis, Ausführung matt (5 gloss), kratzfes / Peinture à base d'eau, finition mate (5 gloss), anti-rayures / Pintura a base de agua, acabado mate (brillo 5), anti-arañazos



Lacquered visible grains

Laccato poro aperto / Laqué pore ouvert / Offenporig lackiert / Lacado poro abierto



• SEAT - SEDUTA - SITZ - ASSISE - ASIENTO

Seat in beech plywood, padded with expanded, flexible polyurethane (variable density 40-60kg/m), fire-retardant (class 1 IM, Crib 5), covered with fabric

Sedile in multistrato di faggio, imbottito con poliuretano espanso flessibile (doppia densità 40-60 kg/m³), ignifugo (classe 1 IM, Crib 5), rivestita in tessuto / Sitz aus Eschen-Multiplex, gepolstert mit flexiblem Polyurethan (doppelte Dichte 40-60 kg/m³), feuerfest (Klasse 1 IM, Crib 5), und mit Stoff bezogen / Assise en multiplis de hêtre, rembourrée en polyuréthane expansé flexible (double densité 40-60 kg/m³), ignifuge (classe 1 IM, Crib 5), recouverts de tissu / Asiento en contrachapado de haya, tapizada de espuma de poliuretano flexible (doble densidad 40-60 kg/m³), ignífugo (clase 1IM, Crib 5), forrado de tela

FABRIC - TESSUTO - STOFF - TISSU - TEJIDO

Cat. A - C - D40+D44 - E - G - H - P

• FRAME - SUPPORTO - ABSTÜTZUNG - SUPPORT - SOPORTE

Die-cast aluminium

Pressofusione d'alluminio / Aluminium-Druckguss / Aluminium moulé sous-préssion, vernissage à poudre époxy-polyester / Fusión de aluminio

FRAME FINISH - FINITURA SUPPORTO - AUSFÜHRUNG DES ABSTÜTZUNG - FINITION SUPPORT - ACABADO SOPORTE

Powder coating*

Verniciato con polvere / Pulverbeschichtet / Époxy à poudre / Barnizado con polvo

* See legend finishes on website
Vedi legenda finiture sul sito web

Polished aluminium

Alluminio lucidato / Aluminium poliert / Aluminium Poli / Aluminio Pulido



FEET - PIEDINI - GLEITER - PATINS - TACOS

Feet with interchangeable insert in felt type "15", suitable for delicate and sensitive floors (wood, ceramics, marble)

Piedini con inserto intercambiabile in feltro tipo "15", adatti per pavimenti delicati e sensibili (legno, ceramica, marmo) / Gleiter mit austauschbarem Einsatz aus Filz Typ „15“, geeignet für empfindliche und weiche Böden (Holz, Keramik und Marmor) / Patins avec insert interchangeable en feutre type "15", pour sols délicats et sensibles (bois, marbre, céramique) / Tacos con inserto intercambiabile de feltro tipo "15", aptos para pisos delicados y sensibles (madera, cerámica, mármol)

ACCESSORIES Accessori Zubehör Accessoires Accesorios	code KIT/PIEDINO.00.003_100 Polypropylene foot insert Ø17,black, suitable for moquette, carpets, concrete and metal Inserto piedino in polipropilene Ø17,nero, adatto per moquette, tappeti, cemento e metallo / Einsatz für Gleiter aus Polypropylen Ø 17, schwarz, geeignet für Teppichboden, Teppich, Zement oder Metall / Embout de pied en polypropylène Ø17,noir, convient aux moquettes, tapis, béton et métal / Inserto taco de polipropileno Ø17,negro, aptos para moqueta, alfombras, hormigón y metal
REGULATIONS AND CERTIFICATES Normative e Certificazioni Bestimmungen und Zertifikat Normatives et certifications Normativas y certificados	Conforming to: seat and back static load test EN 1728 - EN 16139, level L2 - extreme Conforme alla norma: carico statico sul sedile-schienale EN 1728 - EN 16139, livello L2 - estremo Conforming to: combined seat and back fatigue test, 200.000 cycles EN 1728 - EN 16139, level L2 - extreme Conforme alla norma: resistenza a fatica del sedile-schienale, 200.000 cicli EN 1728 - EN 16139, livello L2 - estremo FSC CERTIFICATE - CERTIFICATO FSC Certificate Registration SA - COC - 003864 License Code FSC - C114358 Wooden coming from FSC 100% monitored and safeguarded forests Legno proveniente da foreste controllate FSC 100% / Holz aus FSC 100% - kontrollierten Wäldern geerntet / Bois provenant des forêts contrôlées FSC 100% / Madera extraída de bosques controlados por el FSC100% 77% demountable product - 76% recyclable material Prodotto 77% disassemblabile - 76% materiali riciclabili / Produkt 77% demontierbar - 76% Material recyclingfähig / Produit 77% démontable - 76% recyclable / Producto 77% desmontable - 76% materiales reciclables



The mark of
responsible forestry
FSC® C114358