

Pedrali SpA

SP 122 - 24050 Mornico al Serio - Bergamo - Italia

Ufficio Commerciale Italia +39 035 8358810

Export Dept. +39 035 8358840



Fax +39 035 8358888

www.pedrali.it - info@pedrali.it



MALMÖ 246_ST

design Michele Cazzaniga - Simone Mandelli - Antonio Pagliarulo



MC 0,29



Kg

MATERIALI

Materials / Materialien / Matériaux /
Materiales

- SEDUTA / SEAT / SITZ / ASSISE / ASIENTO

Sgabello in frassino, imbottita in poliuretano flessibile (densità 60 kg/m³) / Ash stool, upholstered in flexible expanding polyurethane (60 kg/m³ density) / Hocker aus Eschenholz, Polyurethanschaum (Dichtigkeit 60 kg/m³) / Tabouret en frêne, rembourré en polyuréthane souple (densité 60 kg/m³) / Taburete de fresno, Tapizado con espuma de poliuretano flexible (densidad 60 kg/m³)

- TESSUTO / FABRIC / STOFF / TISSU / TEJIDO

Cat. C - H - G - P

- FINITURA / FINISH / AUSFÜHRUNG / FINITIONS / ACABADO



FR AN GC

- POGGIAPIEDI / FOOTREST / FUßRASTE / REPOSE-PIEDS / REPOSA PIES

Acciaio Inox AISI 304, tubo Ø16 mm, satinato / Stainless steel AISI 304, tube Ø16 mm, satinized / Edelstahl AISI 304, Rohr Ø16 mm, Satiniert / Acier inox AISI 304, tube Ø16 mm, satiné / Acero inoxidable AISI 304, tubo Ø16 mm, satinado

UTILIZZO

Use / Verwendung / Emploi / Uso

Contract, indoor

NORMATIVE e CERTIFICAZIONI

Regulations and certificates /
Bestimmungen und Zertifikat /
Normatives et certifications /
Normativas y certificados

Conforme alla norma: carico statico sul sedile-schienale EN 1728:2012 - EN 16139:2013, livello L2 - estremo

Conforming to: seat and back static load test EN 1728:2012 - EN 16139:2013, level L2 - extreme

Conforme alla norma: resistenza a fatica del sedile-schienale, 200.000 cicli EN 1728:2012 - EN 16139:2013, livello L2 - estremo

Conforming to: combined seat and back fatigue test, 200.000 cycles EN 1728:2012 - EN 16139:2013, level L2 - extreme

Conforme alla norma: resistenza a fatica appoggia piedi, 100.000 cicli EN 1728:2012 - EN 16139:2013, livello L2 - estremo

Conforming to: foot rest durability test, 100.000 cycles EN 1728:2012 - EN 16139:2013, level L2 - extreme

Omologazione Ministeriale «Serie Malmö» - Classe 1 IM - tessuto G59+G69 / Ministerial type approval «Malmö series» - Class 1 IM - fabric G59+G69 / Ministerial Zulassung «Serie Malmö» - Klasse 1 IM - Stoffe G59+G69 / Homologation Ministérielle «Série Malmö» - Classe 1 IM - tissu G59+G69 / Homologación Ministerial «Serie Malmö» - Clase 1 IM - tela G59+G69



The mark of
responsible forestry
FSC® C114358