

Pedrali SpA

SP 122 - 24050 Mornico al Serio - Bergamo - Italia

Ufficio Commerciale Italia +39 035 8358840

Export Dept. +39 035 8358840


Fax +39 035 8358888

[www.pedrali.it](http://www.pedrali.it) - [info@pedrali.it](mailto:info@pedrali.it)

**RIPIANO / TOP / TISCHPLATTE / PLATEAU / SOBRE**

**BAI/50**

design Pedrali R&D



|   |  |
|---|--|
| <b>STRATO SUPERFICIALE</b><br>Material / Material / Matériau / Material | <b>Laminato, finitura gofrata</b><br>Laminate, textured finish / Laminatplatte, texturisiert / Stratifié, finition gaufrée / Laminado, acabado gofrado   |
| <b>ANIMA</b><br>Core / Kern / Coeur / Alma                              | <b>MDF</b>   |
| <b>BORDO</b><br>Edge / Kante / Chant / Canto                            | <b>Piatto, in ABS bianco</b><br>Flat, white ABS / Flache, ABS weisse/ Plat, ABS blanc / Recto, ABS blanco  |
| <b>SPESSORE</b><br>Thickness / Stärke / Épaisseur / Espesor             | <b>50 mm</b>   |
| <b>MISURE</b><br>Sizes / Abmessungen / Dimensions / Medidas             | * <u>Tolleranza dimensionale ± 5 mm</u><br><b>Tondo</b> / Round / Runder / Rond / Redondo :<br>Ø490 mm - Ø590 mm - Ø690 mm - Ø790 mm - Ø890 mm - Ø990 mm - Ø1190 mm - Ø1290 mm<br><b>Quadrato</b> / Square / Viereckig / Carré / Cuadrado :<br>590x590 mm - 690x690 mm - 790x790 mm - 890x890 mm<br><b> Rettangolare</b> / Rectangular / Rechteckig / Rectangulaire / Rectangular :<br>1190x790 mm - 1390x790 mm - 1590x790 mm   |
| <b>UTILIZZO</b><br>Usage / Verwendung / Usage / Uso                     | <b>Indoor</b>  |
| <b>NORMATIVE</b><br>Regulations / Bestimmungen / Normative / Normativas | <b>Resistenza all'abrasione EN 438-2.10 (Giri IP ≥ 150 e A ≥ 350)</b> / Resistance to surface wear EN 438-2.10 (Revs IP ≥ 150 e A ≥ 350)<br><b>Resistenza al graffio EN 438-2.25 (grado ≥ 3)</b> / Resistance to scratching EN 438-2.25 (rating ≥ 3)<br><b>Resistenza alle macchie EN 438-2.26 (grado 5)</b> / Resistance to staining EN 438-2.26 (rating 5)<br><b>Solidità del colore alla luce EN 438-2.27 (grado ≥ 4)</b> / Lightfastness EN 438-2.27 (rating ≥ 4)<br><b>Resistenza alle bruciature di sigaretta EN 438-2.30 (grado ≥ 3)</b> / Resistance to cigarette burns EN 438-2.30 (rating ≥ 3)<br><br><b>Emissione di formaldeide EN 13986 (E1)</b> / Formaldehyde emission EN 13986 (E1)<br><br><b>Adesione delle finiture al supporto UNI 9240:1987 (3,2)</b><br><b>Rapporto di prova CATAS 106449</b> / Test Catas report 106449 / Testbericht Catas 106449 / Rapport d'essai Catas 106449 / Prueba n° 106449 |